

WORLD BRAND 8830 POLYSTYRENE ADHESIVE

DESCRIPTION

World Brand 8830 is a Polystyrene Foam Contact Adhesive which can be used with steel, aluminium, galvanised iron, wood, hardboard, particleboard, cement sheet, concrete, masonry, expanded polystyrene, insulation batts and fibreglass reinforced plastics. It is suitable for the construction of prefabricated buildings, caravans, mobile homes, sandwich panels, acoustic ceiling tiles and cool rooms.

FEATURES & BENEFITS

- Styrene Safe – will not attack expanded polystyrene.
- Excellent atomization – achieves high coverage rate.

TECHNICAL SPECIFICATIONS

Base	: Synthetic rubber / Resin
Colour	: Light yellowish
Viscosity	: Approximately 400 cps
Solid Content	: 30%
Specific Gravity	: ±0.8
Flash Point	: -28 °C
Flammability	: Highly flammable

PREPARATION

Surfaces should be clean, dry, free from oil, grease, dust and other contaminants. Metal surfaces should be wiped with solvent.

SAFETY PRECAUTIONS

- As adhesive is highly flammable, it should be stored away from heat sources and use in well ventilated areas.
- Beware of vapour as it is harmful by inhalation.

STORAGE

Store product between 10 °C to 25 °C for maximum storage life. Keep containers tightly closed as adhesive tends to skin when exposed to air.

PACKAGING

Available in both 1 US gallon per tin and 5 US gallon per tin.

SHELF LIFE

Minimum of 12 months if stored under above conditions.

The information contained here is true and accurate to the best of our knowledge. The manufacturer makes no warranty or guarantee of results and resume no obligations or liabilities from use of this product.

